

















# Profile 25M & 29 Ducting – Flat metal and rigid plastic ducting systems















## Models

Product Profile 25 (230mm X 25mm)		
<b>FMD</b> Flat ducting 2.4 metre length		89758AA
<b>FMH90</b> Horizontal 90° bend		89759AA
<b>FMTB</b> Transition/air brick		89760AA
<b>FMP</b> Plenum box		89761AA
<b>FMV90</b> Vertical 90° bend		89762AA
<b>FMC</b> Coupling (boxed in 6s)		89764AA

Product Profile 29 (234mm x 29mm)		
<b>XFV90</b> Vertical 90° bend		91110AA
<b>XFV45</b> Vertical 45° bend		91111AA
<b>XFEP</b> Elbow bend/plenum 100mm spigot (female)		91112AA
<b>XFRRR</b> Round to Rec adaptor 100mm spigot (female)		91113AA
<b>XFS</b> Support clip (packs of 10)		91114AA
<b>XFLAA</b> Long airbrick adaptor		91102AA
<b>XFAF</b> Airbrick fascia terracotta		91103AA
<b>XFAS</b> Airbrick soldier course		91246AA
<b>WD100</b> 100mm Ø wall duct		89543AA
<b>XFD</b> Flat channel duct		1m 91104AA
		1.5m 91105AA
		2m 91106AA
<b>XFC</b> Flat channel connector		91107AA
<b>XFH90</b> Horizontal 90° bend		91108AA

# Profile 54, 60 & 90 Ducting – Rigid plastic flat ducting systems

## Models

			Product Profile 54 (110×54mm)		Profile 60 Dims (204×60mm)		Profile 90 Dims (220×90mm)		
Flat ducting		1m	FPD5150		FPD100	89755AA	FPD9100	92325AA	
		1.5m		92451AA	FPD150	91188AA	FPD9150	92315AA	
Coupling			FPC5	92452AA	FPC	89757AA	FPC9	92316AA	
Mounting Bracket			FPB5 (per box of 10)	92519AA	FPB (per box of 10)	89756AA	FPB9 (per box of 10)	92314AA	
Horizontal 90° bend			FPH590	92453AA	FPH90	89754AA	FPH990	92317AA	
Horizontal adjustable bend			FPH545	92456AA	FPH45	89750AA	FPH945	92319AA	
Vertical 90° bend			FPV590	92454AA	FPV90	89753AA	FPV9590	92318AA	
Vertical 45° bend			FPV545	92517AA	FPV45	92537AA	FPV945	92545AA	
T Piece			FPT5	92455AA	FPT	90091AA	FPT9	92515AA	
Flexible Ducting 0.5m			FPF5	92510AA	FPF	91484AA			
Plenum bend		100mm Ø	FPP5100	92457AA	FPP100	89752AA			
		125mm Ø			FPP125	91259AA	FPP125	92321AA	
		150mm Ø			FPP150	91483AA	FPP150	92322AA	
Round to rectangular adaptor			PRA5	92511AA	PRA	91482AA	PRA9	92320AA	
Fire damper collar			PBF5	92514AA	FBF	91975AA	FBF9	92516AA	
Air brick adaptor		Single	FPA5	92513AA	FBA6	92313AA			
		Double			FPA	92573AA	FPA9	92323AA	
Wall outlet grille		Single				FPG	89751AA		
		Double				FPG9	92324AA	FPG9	92324AA

# Ducting Models



Flexible Ducting Xflex FD

	Dia (mm)	Length (m)	
FD100	100	3	89663AA
		6	89669AA
FD125	125	3	89664AA
		6	89670AA

Commercial Diameters			
FD150	150	3	89665AA
		6	89671AA
FD200	200	3	89666AA
		6	89672AA
FD250	250	3	89667AA
		6	89673AA
FD315	315	3	89668AA
		6	89674AA

Glass fibre fabric on a PVC coated close pitch steel wire helix. 54 minute fire integrity from within as measured to BS 476: Part 20 – (1987) | Can be interlocked and sealed with duct tape to form an airtight seal | Attached to spigots using worm drive clips



Insulated Circular Plastic Ducting

	Dia (mm)	Length (m)	
CPD125	125	2	91474AA
CPD150	150	2	91475AA

Uninsulated Circular Plastic Ducting

	Dia (mm)	Length (m)	
CPDN100	100	2	92538AA
CPDN125	125	2	92539AA
CPDN150	150	2	92540AA



New Aluminium Flexible Ducting Xflex ALU

	Dia (mm)	Length (m)	
ALU100	100	10	91435AA
ALU125	125	10	91436AA
ALU150	150	10	91437AA

Commercial Diameters			
ALU200	200	10	91438AA
ALU250	250	10	91439AA
ALU315	315	10	91440AA
ALU400	400	10	91441AA

Tough foil construction on a high strength wire helix | Over 40 minute fire rating BS 476: Part 20 (1987)



Insulated Circular T-pieces

	Dia (mm)	
ICT125	125	91476AA
ICT150	150	91477AA

Uninsulated Circular T-pieces

	Dia (mm)	
ICTN100	100	92550AA
ICTN125	125	92551AA
ICTN150	150	92552AA



Thermal Flexible Ducting Xflex TFD

	Dia (mm)	Length (m)	
TFD100	100	10	91459AA
TFD125	125	10	91460AA
TFD150	150	10	91461AA

Commercial Diameters			
TFD200	200	5	89850AA
		10	91462AA
TFD250	250	5	89851AA
		10	91463AA
TFD315	315	5	89852AA
		10	91464AA

Double skinned insulated aluminium duct with high density fibreglass insulation to minimise condensation formulation | 25 minute fire integrity from within as measured to BS 476: Part 20 – (1987)



Insulated Circular Plastic 45° Bends

	Dia (mm)	
CPE125	125	91480AA

Uninsulated Circular Plastic 45° Bends

	Dia (mm)	
CPEN100	100	92542AA
CPEN125	125	92543AA

# Ducting & Accessories

## Models



Insulated Circular 90° Bends

	Dia (mm)	
CPCDN100	100	92538AA
CPCDN125	125	92539AA



Y Piece Splitters YPS

	Duct Dia (mm)	
YPS1	100x100x100	91281AA
YPS1.25	100x100x125	92243AA
YPS2	100x100x150	91282AA
YPS3	125x125x125	91283AA
YPS4	125x125x150	91284AA
YPS5	150x150x150	91285AA
YPS6	150x150x200	91286AA
YPS10	250x250x250	91290AA
YPS11	250x250x300	91291AA

Fire retardant ABS moulded splitters |  
Leading lip for improved fixing to flexible  
ducting | Space saving two component  
construction



Autoflow 100

Passive Air Input Unit	91296AW
------------------------	---------

Self regulating, adjusts airflow with outside  
temperature | Range -5 – +10°C | White  
ABS material | Telescopic wall tube 270mm



Circular Plastic Connectors

	Dia (mm)	
CPC100	100	92535AA
CPC125	125	91485AA
CPC150	150	91486AA



Profile 150 Wall Cowl 92436AA

Black metal wall cowl with square mesh



Profile 150 Roof Cowl 91277AA

Complete with flashing for roof pitches  
25 – 45°C | For Xcell MVHR installations  
(2 required)



Bull-nose Vent Grille


BVG100SS	92486AA
----------	---------

100mm dia stainless steel



Circular Plastic Adaptors

	Dia (mm)	
CPA125/100	125	91487AA
CPA150 /125	150	91488AA
CPA180/150	180	92520AA
CPA200/150	200	91489AA



Coweled Outlet

CO100SS	92484AA
---------	---------

100mm dia stainless steel with non-return flap




Wall Grille Gravity Vent

GV100SS	92485AA
---------	---------

100mm dia stainless steel

Accessories  
Models



Extract Grilles

For use in en-suites, bathrooms, kitchens and utility rooms.

RegulAir ceiling spigot XECS

Factory set to the exhaust volume requirement for a room | No site balancing is necessary and the performance cannot be tampered with after insulation | Pushed into the 125mm ceiling adaptor after decorating is complete as part of the second fix | Additional fixings not necessary | Complete with rubber seal

RegulAir XEE  
8-16 bathroom/  
utility grille

91442AA

Preset volume regulator. 8l/s trickle ventilation | Electric damper opens to 16l/s



Circular Air Valves CAV

	Dia (mm)	
CAV100	100	89682AA
CAV125	125	91490AA
CAV150	150	89683AA

Valve has adjustable centre disc | Multi-inlets/outlets | Flexible ducting (FD) can be terminated at the valve

Circular Air Valves CAV FD

	Dia (mm)	
CAV125FD	125	91495AA

Circular air valve with integral fire damper



Wall Ducts WD

	Duct Dia (mm)	
WD100	100	89543AA
WD125	125	89703AA
WD150	150	89704AA
WD200	200	89705AA
WD250	250	89706AA
WD315	315	89707AA

For bridging cavities or lining solid exterior walls



Glass Mounting Kits GMK & DXDG

GMK	90546AA
DXDG	07439AA

Used for installing Premier DX200 and CF20 models in a window | Glass thickness: 4 – 28mm

Allows DX100/LV100 to be mounted in double-glazed panels from 6 – 46mm thick



Input Grilles

For use in bedrooms, halls and living rooms etc.

RegulAir XEI 125 input grille	91451AA
----------------------------------	---------

Hinged diffuser 125 with a distribution pattern allowing installation in the corner of the room | 125mm diameter to fit into RegulAir ceiling adaptor | Also available in 100mm dia

RegulAir XEI 100 input grille	91450AA
----------------------------------	---------



XEV8 8l/s

91448AA

RegulAir XEV induct constant airflow valve | Duct mounted regulator maintains a constant return flow volume to bedrooms etc. | Fits 125mm Profile 150 or Xflex duct



Condensation Trap XCT100

XCT100	89749AA
--------	---------

For use with 100mm dia ducting | Prevents condensed water running back down the duct towards the fan in vertical PVCu pipe ducted applications (not suitable for use in a flexible duct run) | Collected water must be piped to a convenient disposal point | Colour: Grey | 20mm drain off point | Material: PVCu | Length: 85mm

# Accessories

## Models



Worm Drive Clips WDC

	Dia (mm)	
WDC5	100 – 125	89684AA
WDC8	150 – 200	89685AA
WDC13	250 – 315	89686AA

Steel clips for connecting flexible ductwork to spigots | Supplied in packs of 10



Ceiling Kit XCMK

XCMK	90066AA
------	---------

Allows a sealed ceiling mounting of ducted products | Complete with ceiling adaptor tube 105.7mm dia, rubber gasket and foam strip | Used with: Premier DX200, DX400



GX Wall Kits WK

	Dia (mm)	
WK6/8	200 (GX6)	89369AA
WK6/11	280 (GX6)	89370AA
WK9/8	200 (GX9)	89371AA
WK9/11	280 (GX9)	89372AA
WK12/8	200 (GX12)	89373AA
WK12/11	280 (GX12)	89374AA

For bridging cavity walls and lining double brick walls | Steel wall liner | Length: 200mm and 280mm | Set of 508mm ladder strips



Premier Grease Filters PDXGF

Premier 200 range

PDXGF	90548AA
PDXGF4	91145AA


For Premier units in kitchen applications | Fits behind the inlet | Material: self extinguishing black polyester foam



Vent Cowl VC

VC10	89531AA
------	---------

Provides weather protection for a 100mm PVC rigid ducted outlet | Pushfit and should be secured with solvent adhesive | Material: PVCu | Colour: Grey | Used with: Premier DX200, DX400, DX100 axial models in exposed situations | Cowl diameter: 200mm | wØ201 x h101 x inner Ø110mm



Extendable Interlocking Wall Kits WK6

WK6/300	90085AA
WK6/450	90086AA

For bridging cavity wall constructions, or lining solid double brick walls | Interlocking facility to build up to required length | Available in 300mm or 450mm lengths | Complete with 508mm ladder strips



Air Replacement Door Grilles  
DG-W DG-B

	Colour	
DG-W	White	89529AA
DG-B	Brown	89530AA

Tight closing bathroom/toilet doors prevent air circulation to the fan | Air replacement grilles permit air to flow into the room with the door shut | Slimline design | Consists of two grilles and fixings | Minimum door thickness 35mm | Dimensions: w454 x h90mm overall, w435 x h77mm hole

Accessories  
Models



Wall Vent Kit  
VK10

89120AW

To bridge a cavity or line a solid wall hole  
| Complete with wall duct (WD), 155mm square external back-draught shutter, foam strip and wall fixings | Grille w155 x h155mm | Wall hole Ø117mm



Airbrick Adaptor  
XAA

89777AA

A fabricated GSM 340mm sleeve to bridge a cavity and line a solid wall | Connects to 100mm duct | Includes an air brick | GSM adaptor | Used with all 100mm fans | w220 x h65 x d340 Ø100mm



Wall Kit XXSWK4

90333AW

100mm wall kit consists of wall duct, internal and external grille foam strips and wall fixings | Used with: XXS100 | Wall hole Ø117mm



Exterior Storm Cowl XXSCW & XXSCB

	Colour	
XXSCW	White	90461AW
XXSCB	Brown	90462AB

Provides protection against severe backdraughts and water ingress | Fitted with gravity flap damper | Wall mounted | 100mm spigot | Used with: 100mm axial fans



Wall Grille Gravity Shutter XXWG4

Colour	
Grey	89687AA
White	89538AA

Protected duct outlet fitted with gravity flaps | Ø100mm connection | Dimensions: w155 x h155 x d15mm



Louvred Wall Grille LG

	Dia (mm)	
LGW125	125	91492AA
LGB125	125	91493AA


Available in white and brown



Fire Damper XFC

	Dia (mm)	
XFC100	100	89843AA
XFC125	125	89844AA
XFC150	150	89845AA
XFC200	200	89846AA

For ducts, walls and ceilings | Should not be fitted into flexible ducting | Wall or duct in which XFC is fitted should have a rated fire integrity in accordance with Building Regulations Part B | Provides full 1 hour fire check | Closing temperature 72°C | Low temperature drop | Tested at Warrington Fire Research Centre to BS476 Part 20



Roof Mounting Plates XRP

XRP6 (RX6)	00370AK
w592 x h542 x d89 Ø105mm	
XRP9 (RX9)	00371AK
w774 x h774 x d101 Ø257mm	

Provides effective and secure installation in flat roof applications | Flame-retardant resin bonded fibre glass | Requires the installer to build a kerb onto which plate is fixed | Always use sealant to bed in the outer cowl seal for weatherproof joint | Colour: black



Wall Grille CFWG

	Colour	
CFWG100	Grey	89215AB
CFWG100	White	89742AW
CFWG150	Grey	89690AB
CFWG150	White	89857AW

Surface-mounted exterior wall outlet grille | For use with 100mm/150mm nominal size ducting | Fixing screws provided | Use with: 100mm axial variants | Dimensions: w150 x h150 x d13mm (CFWG100), w217 x h217 x d24mm (CFWG150)

## Accessories Models



### Termination Ducting Kit WT

	Dia (mm)	
WT10	100	89538AA
WT15	150	89687AA


For through-wall application | Complete with exterior grill, wall duct and spigot plate | Ducting can be attached to spigot | Wall hole Ø117mm



### Darkroom Cowl DC9

98409AK

For use in scientific and photographic applications | Replaces the outer grille on GX9 and GXC9 models | Roof, window or wall mounting | Hole Ø257mm | Colour: black | Use with: GX9, GXC9. w475Ø d144 x 117mm



### Solid Duct Fasteners XMK

	Duct Dia (mm)	
XMK100	100	89618AA
XMK125	125	89619AA
XMK150	150	89620AA
XMK200	200	89621AA
XMK250	250	89622AA
XMK315	315	89623AA

For connecting XID and XIDP fans to rigid ductwork | Supplied in pairs | Metal clamping band with vibration absorbent foam



### Easy-Fix Termination Kit EFT

90427AA

Designed to be installed from inside a building through a cored out to Ø115mm (nominal) hole drilled in brickwork | Easily cut to length | Simple installation save times and cost | Four sealing rings provide a watertight seal in the external wall | Used with: Premier DX200, CF20 | Not suitable for 100mm axial fans | Length: 465mm



### Roof Cowls RC

RC6 (GX6, GXC6)	89997AW
RC9 (GX9, GXC9)	90048AW
RC12 (GX12)	90092AW

### Roof Cowls XRC

XRC315-350	92364AA
------------	---------

Ø315 – 350mm Roof Cowl

XRC400-450	92365AA
------------	---------

Ø400 – 450mm Roof Cowl

XRC500-550	92366AA
------------	---------

Ø500 – 550mm Roof Cowl

XRC630-710	92367AA
------------	---------

Ø630 – 710mm Roof Cowl

For use in roof applications | The cowl is fitted in place of an exterior grille | Can also be used in exposed window or wall applications subject to strong prevailing winds



### Ceiling Diffuser Grilles DG

#### Square – Satin Silver

	Dia (mm)	
DG20S	200	89816AA
DG30S	300	89818AA

#### Square – White

	Dia (mm)	
DG20W	200	89815AW
DG30W	300	89817AW

For air input systems terminating at ceilings and internal walls | Adjustable grille vanes to set up direction of airflow for a particular area | Fixing screws provided (not size 600) | Use with grille boxes and Xflex ducting | Aluminium construction | Colours: satin silver or white

### 4-Way Diffuser

DG50W	89821AW	£143.90
-------	---------	---------



### Air Operated Louvre Shutters XLG

	Square (mm)	
XLG100	100	89691AA
XLG120	120	89692AA
XLG150	150	89693AA
XLG200	200x200	89694AA
XLG250	250x250	89695AA
XLG315	315x315	89696AA
XLG400	400x400	90294AA

Plastic construction | Fixed to outside of exterior wall | Air operated | Colour: white



Accessories  
Models



Fire Blocks FB

FB20	89835AA
------	---------

w200 x h200mm

FB30	89836AA
------	---------

w300 x h300mm

For use with air replacement grille (ARG) | Fitted between two grilles in a fire door or compartment | Spec fire rated 60 mins to BS478 Part 8



Protective Wall Grilles PG

PG6 (GX6, GXC6, WX6)	89375AA
PG9 (GX9, GXC9, WX9)	89376AA
PG12 (GX12)	89377AA
PGW12 (WX12)	90204AA

For use with GX and WX fans to protect the exterior grille from damage by vandals | Constructed from steel mesh and finished in black epoxy powder paint | Surface-mounted to exterior wall using fixing screws and wall plugs provided | w356 x h305 x d67mm



Grille Box GB

	Duct Dia (mm)	Square	
GB20/100	100	200	89676AA
GB20/125	125	200	89677AA
GB20/150	150	200	89678AA
GB30/200	200	300	89679AA
GB45/315	315	450	89681AA
GB50/315	315	500	89828AA
GB60/400	400	600	90296AA

Used in conjunction with egg-crate ceiling grille and ceiling diffuser grille to connect to ductwork | Use Xflex FD or TFD to attach to spigot and secure with worm drive dip



100mm Inside Fit External Wall Grille

As kit with flexible ducting	
Round/White	92991AW
Square/White	92992AW
Round/Brown	92993AB
Square/Brown	92994AB
Retail blister pack x6	
Round/White	93238AA
Square/White	93236AA
Round/Brown	93239AA
Square/Brown	93237AA



Air-Replacement Grilles ARG

ARG20	89833AA
-------	---------

w200 x h200mm

ARG30	89834AA
-------	---------

w300 x h300mm

For use with all commercial fans | Fitted to doors or partition walls to provide adequate air replacement for a fan | Can be used in conjunction with Fire Block FB in fire doors and panels to prevent the breach of fire protected areas or compartments | Each set comprises of 2 grilles



150mm Inside Fit External Wall Grille

As kit with flexible ducting	
Round/White	93191AB
Round/Brown	93191AB
Retail blister pack x6	
Round/White	93240AA
Round/Brown	93241AA



Simply Silent™ Replacement Baffle

SSSB Square	92957AW
SSRB Round	92958AW

## Accessories Models



**Spigot Plates SP**

	Duct Square Dia (mm)		
<b>SP100</b>	100	180	92644AA
<b>SP125</b>	125	175	89698AA
<b>SP200</b>	200	250	92647AA
<b>SP250</b>	250	300	92648AA
<b>SP315</b>	315	365	92649AA

Fixes to the interior surface of wall to connect to Xflex ducting | Connect duct using worm drive clips | Material: metal



**Air Volume Dampers AVD**

	Square (mm)	
<b>AVD20</b>	200	89829AA

Clips directly to an egg-crate grille or ceiling diffuser grille to adjust the volume of air entering the room | Lever adjustment | Depth 44mm | Used together with Grille Box and Xflex ducting | Material: Aluminium Mill finish



**GX Longer Length Ladder Strips**

<b>GXL20 (20 pack)</b>	89382AA
<b>GXL50 (50 pack)</b>	89383AA

Used when installing GX fans through walls | Length: 508mm | Easy to cut | GX6 & GXC6: 2 strips | GX9 & GXC9: 3 strips | GX12: 4 strips



**Egg-crate Ceiling Grilles CG**

Square – Satin Silver		
	Dia (mm)	
<b>CG20S</b>	200	89675AA
<b>CG30S</b>	300	89532AA
<b>CG45S</b>	450	89533AA
<b>CG50S</b>	500	89827AA
<b>CG60S</b>	600	90295AA

Square – White		
	Dia (mm)	
<b>CG20W</b>	200	89823AW
<b>CG30W</b>	300	89824AW
<b>CG45W</b>	450	89825AW
<b>CG50W</b>	500	89826AW


Can be used on ceilings or internal walls as an air replacement grille with large free area | Aluminium construction | Fixing screws provided (not size 600) | Use with grille boxes and Xflex ducting | Colours: satin silver or white



**External Louvre Grilles EG**

	Duct (mm)	
<b>EG30</b>	300x300	89534AA
<b>EG45</b>	450x450	89535AA
<b>EG50</b>	500x500	90538AA
<b>EG67</b>	670x670	90539AA


Weather-resistant, recess-mounting fixed louvre grille for exterior walls | Aluminium construction | Fitted bird guard



**Backdraught Shutters XBD**

	Duct Dia (mm)	
<b>XBD100</b>	100	89636AA
<b>XBD125</b>	125	89637AA
<b>XBD150</b>	150	89638AA
<b>XBD200</b>	200	89639AA
<b>XBD250</b>	250	89640AA
<b>XBD315</b>	315	89641AA

GSM construction | Spring loaded flaps | For use with XID, XIDP and cabinet fans | Fits between two lengths of ducting which are secured to the outside with worm drive clips when using Xflex FD ducting or with solid duct fasteners for solid ducting



**Bag Filter Cassettes CFC**

	Duct Dia (mm)	Box Sq. (mm)	
<b>CFC1-125</b>	125	155	90285AA
<b>CFC2-150</b>	150	180	90286AA
<b>CFC3-200</b>	200	230	90287AA
<b>CFC4-250</b>	250	280	90288AA
<b>CFC5-315</b>	315	345	90289AA
<b>CFC6-400</b>	400	430	90290AA

GSM construction | Simple but effective inline filtration | Filter medium EU3 | 92% efficient to BS 2831 number 2 test | All filter boxes are 130mm deep | Lid secured by screw on 2 sides

Accessories  
Models



Air Operated Louvre Shutters XLS

	Duct (mm)	
XLS315	315x315	89905AA
XLS350	350x350	91144AA
XLS400	400x400	89906AA
XLS450	450x450	89907AA
XLS500	500x500	90540AA
XLS670	670x670	90541AA

Aluminium construction | Fixed to outside of exterior wall | Air operated | Use with: XPM



Four Way Ceiling Diffusers FW

	To Fit Square Duct Size (mm)	
FW225	225x225	91424AA
FW300	300x300	91425AA
FW500	500x500*	91429AA

\*Outer frame dim. 600x600 | Rigid lightweight polypropylene frame | Four drop-in diffuser cassettes can be set up for angled or downward diffusion | Each cassette can be fitted eight ways providing multi-directional air patterns | Secret fixings adjust to varying plasterboard and tile thickness without surface screws | Largest size drops into 600x600mm ceiling grid system



Spigot Plate/Damper FWS

	Diff Square (mm)	Spigot Dia (mm)	
FWS150	225x150	150	91430AA
FWS200	225x200	200	91431AA
FWS250	300x250	250	91432AA
FWS300	350x300	300	91456AA

Interlock with four-way diffusers | Sloping spigot and barbs for easy duct attachment | Built-in air volume damper in spigot sizes up to 300mm



Flexible Duct Connectors

FFC1-125	90297AA
Ø125mm flexible duct connector	
FFC2-150	90298AA
Ø150mm flexible duct connector	
FFC3-200	90299AA
Ø200mm flexible duct connector	
FFC4-250	90300AA
Ø250mm flexible duct connector	
FFC5-315	90301AA
Ø315mm flexible duct connector	
FFC6-400	90302AA
Ø400mm flexible duct connector	



Short Case Axial Fan Xtras SCX

	Fan Size (mm)	
SCX315	(XSCA315)	91317AA
SCX350	(XSCA350)	91318AA
SCX400	(XSCA400)	91319AA
SCX450	(XSCA450)	91320AA
SCX500	(XSCA500)	91321AA
SCX630	(XSCA560)	91322AA

Installation pack comprising of: 2 steel matching coupling flanges | 2 flexible connectors | 4 worm drive clips | 2 mounting feet | 4 anti-vibration mounts



Circular Silencers SIL

	Duct Dia (mm)	Lgth (mm)	Dia (mm)
SIL100	100	300	200
89837AA			
SIL125	125	300	225
89838AA			
SIL150	150	300	250
89839AA			
SIL200	200	300	300
89840AA			
SIL250	250	300	350
89841AA			
SIL315	315	300	415
89842AA			

For use with all circular duct systems | For rigid ductwork the spigot incorporates a duct seal for leak-free construction | GSM construction