## **Engine 68-400**

## Optimyst®



Dimplex Engines are designed to create your quality fireplace inside a wall or surround, exactly where you want it, finished to fit your personal taste and easy to use. Not only offering the unrivalled Optimyst® flame effect but also the comfort of a thermostatic heater. Thanks to its smart 24/7 timer, it is ready to welcome you with a cozy atmosphere at any moment. The vertical shape of the Engine 68-400 allows a good view on its uprising flames. The optional black mirror back panel adds to this.

## USP's


- Insert fireplace designed to fit into a custom-made frame or fireplace
- Easy-fill water tank, offers around 8-10 hours of continuous operation before refilling is required
- Enjoy the ambiance of the flames with or without the heater for all year round comfort
- 24/7 timer ensures a high flexibility, each day of the week can be set individually
- Optional: mirror back panel for an even more intense fire experience




Article number: 210258 | EAN Code: 5011139210258 | Optimyst®









MODEL	Ή′	'W'	<b>'X'</b>	'Y'
ENG56-400	700mm	490mm	413mm	395mm
ENG68-400	823mm	490mm	413mm	517mm
ENG56-600	700mm	646mm	569mm	395mm

		Engine 68-400	
	Fire system	Optimyst®	
	Article number	210258	
	EAN code	5011139210258	
General specifications	Model	Built-in unit	
Control of Control of Control	View of the fire	1 sided	
	Colour	Black achterpaneel (option: Back wall mirror)	
	Decoration / fuel bed	Log set	
Product size	Measurements view of the fire (WxH)	41 x 50 cm	
Product size	Outside dimensions WxHxD	49 x 82,5 x 25,5 cm	
	Heat output	Yes	
	Thermostat	Yes	
	Remote control	Yes	
Features	Manual controlling directly at the fireplace possible yes / no	Yes, flame effect on / off	
	Light module	Halogen	
	Sound module	No	
	Colour effects settings	No	
	Heat setting 1 in W	1000W	
Power consumption	Heat setting 2 in W	2000W	
Power consumption	Flame only operation in W	200W	
	Max. consumption	2000W	
Voltage	Voltage/Electrical frequency	230V/50Hz	
	Product weight in kg	16,2	
Specifications	Length of the cord	1,5 m	
	Warranty	2 year	